

# TUBO METALLICO CORRUGATO INOX AISI 316 CON RINFORZO METALLICO INOX AISI 304

## AISI 316 STAINLESS STEEL BRAID CORRUGATED HOSE WITH AISI 304 STAINLESS STEEL BRAID REINFORCEMENT



Riferimento Reference	Ø int. inch. Ø int. inch.	Ø Esterno Ø External mm		Ø Interno Ø Internal mm		Spessore Parete Tape Thickness mm	Pressione di esercizio Working pressure max bar (20°)	R.min.di curvatura Min. bend radius mm	Peso Weight g/m
		min.	max.	min.	max.				
TICI38	3/8"	14,6	16,6	9,8	10,4	0,15	100	38	217
TICI12	1/2"	17,3	19,3	12,0	12,6	0,15	75	45	224
TICI58	5/8"	22,8	24,8	16,0	16,6	0,20	65	58	400
TICI34	3/4"	27,4	29,8	20,0	20,6	0,20	58	70	491
TICI1	1"	33,0	35,6	25,1	25,7	0,20	55	85	747
TICI114	1"1/4"	41,5	44,5	34,0	34,6	0,22	50	105	892
TICI112	1"1/2"	49,8	54,2	39,6	40,4	0,25	40	130	1392
TICI2	2"	62,0	64,6	50,0	51,0	0,25	30	160	1652
TICI212	2" 1/2"	77,0	83,0	65,0	67,0	0,30	24	175	2190
TICI3	3"	91,0	97,0	75,5	78,5	0,30	18	175	2590
TICI4	4"	117,5	123,5	100,5	105,8	0,40	16	250	3860
TICI5	5"	149	155	122,5	127,5	0,40	12	318	5930
TICI6	6"	178	184	148,5	153,5	0,40	10	353	6440
TICI8	8"	228	234	195,0	200,0	0,50	8	456	9900

### Note tecniche:

Temperature di utilizzo: da -200° C a +600° C

### Technical Notes:

Temperature range: -200° C to max +600° C

