



M22512



JIC FEMALE 37° CONE SEAT - SAE J516 / ISO 12151-5 (THRUST-WIRE NUT)
 HEMBRA JIC ASIENTO A 37° - SAE J516 / ISO 12151-5 (TUERCA CON SEGURO)
 DKJ 37° DICHTKOPF (UNF-GEWINDE NACH SAE J516 / ISO 12151-5, GESTIFTETE MUTTER)
 FEMMINA JIC CONO 37° - SAE J516 / ISO 12151-5 (DADO SPINATO)

M22513



JIC FEMALE 37° CONE SEAT - SAE J516 / ISO 12151-5 (SLIP-ON NUT)
 HEMBRA JIC ASIENTO A 37° - SAE J516 / ISO 12151-5 (TUERCA LIBRE)
 DKJ 37° DICHTKOPF (UNF-GEWINDE NACH SAE J516 / ISO 12151-5, HINTERLEGTE MUTTER)
 FEMMINA JIC CONO 37° - SAE J516 / ISO 12151-5 (DADO PASSANTE)

PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
------------	-----------	--	--	--------	------------------	--	--	--	--	--

	DN	inch	Size	T	B	A	C			H ₂
M22513-03-04	5	3/16"	- 03	7/16" - 20	3,0	15,1	9,0			15
M22512-03-05	5	3/16"	- 03	1/2" - 20	4,0	15,5	9,2			17
M22512-04-04	6	1/4"	- 04	7/16" - 20	4,0	15,5	8,2			17
M22512-04-05	6	1/4"	- 04	1/2" - 20	4,0	15,8	9,2			17
M22513-04-06	6	1/4"	- 04	9/16" - 18	4,0	16,5	9,8			19
M22512-05-04	8	5/16"	- 05	7/16" - 20	4,0	15,5	8,2			17
M22512-05-05	8	5/16"	- 05	1/2" - 20	5,5	16,0	9,2			17
M22512-05-06	8	5/16"	- 05	9/16" - 18	7,0	15,7	9,7			19
M22513-05-08	8	5/16"	- 05	3/4" - 16	5,5	16,7	10,7			22
M22512-06-05	10	3/8"	- 06	1/2" - 20	5,5	16,6	9,5			17
M22512-06-06	10	3/8"	- 06	9/16" - 18	7,0	16,1	9,2			19
M22513-06-08	10	3/8"	- 06	3/4" - 16	7,0	17,3	10,7			22
M22513-06-10	10	3/8"	- 06	7/8" - 14	9,3	18,1	12,4			27
M22512-08-08	12	1/2"	- 08	3/4" - 16	9,3	19,9	10,2			22
M22513-08-10	12	1/2"	- 08	7/8" - 14	9,3	18,5	12,4			27
M22513-08-12	12	1/2"	- 08	1.1/16" - 12	12,5	21,8	13,8			32
M22512-10-10	16	5/8"	- 10	7/8" - 14	12,5	19,9	12,3			27
M22513-10-12	16	5/8"	- 10	1.1/16" - 12	12,5	21,7	13,8			32
M22512-12-08	19	3/4"	- 12	3/4" - 16	9,3	21,5	10,2			22
M22512-12-10	19	3/4"	- 12	7/8" - 14	12,5	21,5	12,3			27
M22512-12-12	19	3/4"	- 12	1.1/16" - 12	15,0	22,5	14,2			32
M22512-12-14	19	3/4"	- 12	1.3/16" - 12	15,0	23,1	14,8			36
M22512-12-16	19	3/4"	- 12	1.5/16" - 12	19,8	23,0	15,2			38
M22512-16-12	25	1"	- 16	1.1/16" - 12	15,0	23,3	14,4			32
M22512-16-16	25	1"	- 16	1.5/16" - 12	19,8	23,8	15,2			38
M22512-16-20	25	1"	- 16	1.5/8" - 12	26,0	29,8	16,2			50
M22512-20-20	31	1.1/4"	- 20	1.5/8" - 12	26,0	30,0	16,2			50
M22512-20-24	31	1.1/4"	- 20	1.7/8" - 12	32,0	35,0	18,8			60
M22512-24-24	38	1.1/2"	- 24	1.7/8" - 12	32,0	35,0	18,8			60
M22512-32-24	51	2"	- 32	1.7/8" - 12	32,0	37,0	18,8			60
M22512-32-32	51	2"	- 32	2.1/2" - 12	44,0	35,4	24,0			75