


SAE STANDARD CONNECTIONS

M22711

JIC FEMALE 37° CONE SEAT DOUBLE HEXAGON - SAE J516 / ISO 12151-5 (CRIMPED-BACK NUT)
 HEMBRA JIC ASIENTO A 37° DOBLE TUERCA - SAE J516 / ISO 12151-5 (TUERCA PRENSADA)
 DKJ 37° MIT KONTERSECHSKANT (UNF GEWINDE NACH SAE J516 / ISO 12151-5, VORGEKRIMPT MUTTER)
 FEMMINA JIC CONO 37° DOPPIO ESAGONO SAE J516 / ISO 12151-5 (DADO PRESSATO)

M22711K

JIC FEMALE 37° CONE SEAT DOUBLE HEXAGON - SAE J516 / ISO 12151-5 (CRIMPED-BACK COMPACT NUT)
 HEMBRA JIC ASIENTO A 37° DOBLE TUERCA
 SAE J516 / ISO 12151-5 (TUERCA TIPO COMPACTO PRENSADA)
 DKJ (KOMPAKT) 37° MIT KONTERSECHSKANT
 (UNF GEWINDE NACH SAE J516 / ISO 12151-5, VORGEKRIMPT MUTTER)
 FEMMINA JIC CONO 37° DOPPIO ESAGONO
 SAE J516 / ISO 12151-5 (DADO PRESSATO COMPATTO)



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size		T	B	A	C	H ₁	H ₂
M22711-03-04K	5	3/16"	- 03	7/16" - 20	4,0	20	9		12	15
M22711-04-04K	6	1/4"	- 04	7/16" - 20	4,0	20,5	9		12	15
M22711-04-06K	6	1/4"	- 04	9/16" - 18	7,0	21,6	9,5		14	17
M22711-06-06K	10	3/8"	- 06	9/16" - 18	7,0	22,1	9,5		17	17
M22711-06-08	10	3/8"	- 06	3/4" - 16	9,3	21,7	10,7		19	22
M22711-08-08	12	1/2"	- 08	3/4" - 16	9,3	26,9	10,7		19	22
M22711-08-10K	12	1/2"	- 08	7/8" - 14	9,3	29,6	12,5		22	25
M22711-10-10K	16	5/8"	- 10	7/8" - 14	9,3	29,5	12,5		22	25
M22711-12-12	19	3/4"	- 12	1.1/16" - 12	15	30,1	14,1		27	32
M22711-16-16	25	1"	- 16	1.5/16" - 12	19,8	35,5	15,3		32	38
M22711-20-20	31	1.1/4"	- 20	1.5/8" - 12	26,0	42,0	16,1		41	50
M22711-24-24	38	1.1/2"	- 24	1.7/8" - 12	32,0	46,5	18,6		50	60
M22711-32-32	51	2"	- 32	2.1/2" - 12	42,0	50,5	23,5		65	75