

### M22712K

JIC FEMALE 37° CONE SEAT DOUBLE HEXAGON - SAE J516 / ISO 12151-5 (THRUST-WIRE COMPACT NUT)

HEMBRA JIC ASIENTO A 37° DOBLE TUERCA


SAE J516 / ISO 12151-5 (TUERCA TIPO COMPACTO CON SEGURO)

DKJ KOMPAKT 37° DK MIT KONTERSECHSKANT

(UNF-GEWINDE NACH SAE J516 / ISO 12151-5, GESTIFTETE MUTTER)

FEMMINA JIC CONO 37° DOPPIO ESAGONO

SAE J516 / ISO 12151-5 (DADO SPINATO COMPATTO)



| PART. REF.    | HOSE BORE |       |      | THREAD     | DIMENSIONS<br>mm |      |      |   |                |                |  |
|---------------|-----------|-------|------|------------|------------------|------|------|---|----------------|----------------|--|
|               | DN        | inch  | Size |            | T                | B    | A    | C | H <sub>1</sub> | H <sub>2</sub> |  |
| M22712-03-04K | 5         | 3/16" | - 03 | 7/16" - 20 | 4,0              | 20,5 | 8,2  |   | 12             | 15             |  |
| M22712-04-04K | 6         | 1/4"  | - 04 | 7/16" - 20 | 4,0              | 21,0 | 8,2  |   | 12             | 15             |  |
| M22712-04-06K | 6         | 1/4"  | - 04 | 9/16" - 18 | 7,0              | 24,1 | 9,2  |   | 14             | 17             |  |
| M22712-06-06K | 10        | 3/8"  | - 06 | 9/16" - 18 | 7,0              | 24,6 | 9,2  |   | 17             | 17             |  |
| M22712-08-10K | 12        | 1/2"  | - 08 | 7/8" - 14  | 12,5             | 28,4 | 12,6 |   | 22             | 25             |  |
| M22712-10-10K | 16        | 5/8"  | - 10 | 7/8" - 14  | 12,5             | 29,0 | 12,6 |   | 22             | 25             |  |