


## SAE STANDARD CONNECTIONS


### M24792

90° JIC FEMALE LONG DROP ELBOW 37° CONE SEAT - SAE J516 / ISO 12151-5 (THRUST-WIRE NUT)  
 HEMBRA JIC CODO LARGO DE 90° ASIENTO A 37° - SAE J516 / ISO 12151-5 (TUERCA CON SEGURO)  
 DKJ 90° BOGEN 37° DICKTKOPF (UNF-GEWINDE NACH SAE J516 / ISO 12151-5, GESTIFTETE MUTTER)  
 FEMMINA JIC 90° CONO 37° CURVA LUNGA - SAE J516 / ISO 12151-5 (DADO SPINATO)



### M24793

90° JIC FEMALE LONG DROP ELBOW 37° CONE SEAT - SAE J516 / ISO 12151-5 (SLIP-ON NUT)  
 HEMBRA JIC CODO LARGO DE 90° ASIENTO A 37° - SAE J516 / ISO 12151-5 (TUERCA LIBRE)  
 DKJ 90° BOGEN 37° DICKTKOPF (UNF-GEWINDE NACH SAE J516 / ISO 12151-5, HINTERLEGTE MUTTER)  
 FEMMINA JIC 90° CONO 37° CURVA LUNGA - SAE J516 / ISO 12151-5 (DADO PASSANTE)



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size		T	B	A	C	E	H <sub>2</sub>
M24792-04-04	6	1/4"	- 04	7/16" - 20	4,0	28,5	8,2	45,0		17
M24792-04-05	6	1/4"	- 04	1/2" - 20	4,0	28,5	9,2	45,0		17
M24793-04-06	6	1/4"	- 04	9/16" - 18	4,0	29,5	9,8	55,5		19
M24792-06-06	10	3/8"	- 06	9/16" - 18	7,0	35,5	9,2	55,0		19
M24793-06-08	10	3/8"	- 06	3/4" - 16	7,0	36,5	10,7	61,5		22
M24792-08-08	12	1/2"	- 08	3/4" - 16	9,4	40,6	10,3	61,5		22
M24793-08-10	12	1/2"	- 08	7/8" - 14	9,4	45,0	12,4	65,0		27
M24792-10-10	16	5/8"	- 10	7/8" - 14	12,5	53,5	12,3	65,5		27
M24792-12-12	19	3/4"	- 12	1.1/16" - 12	15,0	62,0	14,2	94,5		32
M24792-16-16	25	1"	- 16	1.5/16" - 12	19,8	77,0	15,2	110,0		38