



M10510

BSP MALE PARALLEL 60° CONE SEAT - BS5200 / ISO 8434-6
 MACHO BSP PARALLELO ASIENTO A 60° - BS5200 / ISO 8434-6
 AGR 60° INNENKONUS (BSP-GEWINDE NACH BS5200 / ISO 8434-6)
 MASCHIO GAS CILINDRICO 60° - BS5200 / ISO 8434-6

PART. REF.	HOSE BORE		THREAD	DIMENSIONS mm						
------------	-----------	--	--------	------------------	--	--	--	--	--	--

	DN	inch	Size	T	B	A	C		H ₁	
M10510-03-02	5	3/16"	- 03	1/8" - 28	3,5	22,5	10,0		14	
M10510-03-04	5	3/16"	- 03	1/4" - 19	5,0	25,0	11,0		19	
M10510-04-02	6	1/4"	- 04	1/8" - 28	3,5	22,5	10,0		14	
M10510-04-04	6	1/4"	- 04	1/4" - 19	5,0	25,5	11,0		19	
M10510-04-06	6	1/4"	- 04	3/8" - 19	8,0	27,0	12,0		22	
M10510-04-08	6	1/4"	- 04	1/2" - 14	11,0	30,0	14,0		27	
M10510-05-04	8	5/16"	- 05	1/4" - 19	5,0	26,0	11,0		19	
M10510-05-06	8	5/16"	- 05	3/8" - 19	8,0	27,5	12,0		22	
M10510-06-04	10	3/8"	- 06	1/4" - 19	5,0	26,0	11,0		19	
M10510-06-06	10	3/8"	- 06	3/8" - 19	8,0	28,1	12,0		22	
M10510-06-08	10	3/8"	- 06	1/2" - 14	11,0	30,6	14,0		27	
M10510-08-06	12	1/2"	- 08	3/8" - 19	8,0	28,1	12,0		22	
M10510-08-08	12	1/2"	- 08	1/2" - 14	11,0	31,1	14,0		27	
M10510-08-10	12	1/2"	- 08	5/8" - 14	14,5	33,1	16,0		30	
M10510-08-12	12	1/2"	- 08	3/4" - 14	17,0	34,1	16,0		32	
M10510-10-10	16	5/8"	- 10	5/8" - 14	14,5	33,1	16,0		30	
M10510-10-12	16	5/8"	- 10	3/4" - 14	17,0	34,1	16,0		32	
M10510-12-08	19	3/4"	- 12	1/2" - 14	11,0	32,0	14,0		27	
M10510-12-12	19	3/4"	- 12	3/4" - 14	17,0	35,5	16,0		32	
M10510-12-16	19	3/4"	- 12	1" - 11	22,5	39,5	19,0		41	
M10510-16-12	25	1"	- 16	3/4" - 14	17,0	36,5	16,0		32	
M10510-16-16	25	1"	- 16	1" - 11	22,5	40,8	19,0		41	
M10510-16-20	25	1"	- 16	1.1/4" - 11	28,5	44,8	20,0		50	
M10510-20-20	31	1.1/4"	- 20	1.1/4" - 11	28,5	46,5	20,0		50	
M10510-20-24	31	1.1/4"	- 20	1.1/2" - 11	33,5	48,5	22,0		55	
M10510-24-24	38	1.1/2"	- 24	1.1/2" - 11	33,5	49,5	22,0		55	
M10510-32-32	31	2"	- 32	2" - 11	46,0	53,9	25,0		70	