


## SAE STANDARD CONNECTIONS

### M14110R\*

NPTF SWIVEL MALE 60° CONE SEAT - SAE J516/J514  
 MACHO NPTF GIRATORIO ROSCA ASIEN TO A 60° - SAE J516/J514  
 AGN 60° INNENKONUS (NPTF-GEWINDE) - SAE J516/J514  
 MASCHIO NPTF CONO 60° GIREVOLE - SAE J516/J514




PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size		T	B	A	C	H <sub>2</sub>	H
M14110-04-02R	6	1/4"	- 04	1/8" - 27	3,0	41,9	10,0			17
M14110-04-04R	6	1/4"	- 04	1/4" - 18	4,0	46,4	14,5			17
M14110-04-06R	6	1/4"	- 04	3/8" - 18	7,0	46,4	14,5			19
M14110-06-04R	10	3/8"	- 06	1/4" - 18	4,0	50,5	14,5			22
M14110-06-06R	10	3/8"	- 06	3/8" - 18	7,0	50,5	14,5			22
M14110-06-08R	10	3/8"	- 06	1/2" - 14	9,3	55,2	19,2			24
M14110-08-06R	12	1/2"	- 08	3/8" - 18	7,0	51,5	14,5			27
M14110-08-08R	12	1/2"	- 08	1/2" - 14	9,3	59,0	19,2			27
M14110-12-12R	19	3/4"	- 12	3/4" - 14	16,0	57,9	19,2			32
M14110-16-16R	25	1"	- 16	1" - 11,5	19,8	65,8	24,2			38

\* Not to be used as a live swivel / No usar como una pieza giratoria viva / Nicht zu benutzen als Drehverschraubung / Da non usare come applicazione rotante

### M22812

NPSM FEMALE 60° CONE - SAE J516/J514 (THRUST-WIRE NUT)  
 HEMBRA NPSM ASIEN TO A 60° - SAE J516/J514 (TUERCA CON SEGURO)  
 DK NPSM 60° KONUS - SAE J516/J514 (NPTF-GEWINDE, GESTIFTETE MUTTER)  
 FEMMINA NPSM CONO 60° - SAE J516/J514 (DADO SPINATO)



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size		T	B	A	C	H <sub>2</sub>	H
M22812-04-04	6	1/4"	- 04	1/4" - 18	4,0	17,5	4,2			19
M22812-06-04	10	3/8"	- 06	1/4" - 18	4,0	18,0	4,2			19
M22812-06-06	10	3/8"	- 06	3/8" - 18	7,0	20,9	6,0			22
M22812-08-08	12	1/2"	- 08	1/2" - 14	9,3	22,8	6,5			27
M22812-12-12	19	3/4"	- 12	3/4" - 14	15,0	24,5	9,0			32
M22812-16-16	25	1"	- 16	1" - 11,5	19,8	27,3	10,5			38