

T 340AH



Technical Characteristics

Steam 18 bar (270 psi) - Steel braided

Tube: black conductive EPDM.

Reinforcement: one or two high tensile steel wire braids.

Cover: red EPDM - heat, abrasion and ozone resistant - pin pricked.

Application: saturated and superheated steam.

Constant operation: -40 °C +210 °C (-40 °F +410 °F)
intermittent to 232 °C (450 °F)

Internal Diameter		Outside Diameter		Maximum Working Pressure		Minimum Burst Pressure		Minimum Bend Radius		Weight	
mm	in	mm	in	bar	psi	bar	psi	mm	in	kg/m	lb/ft
13,0	1/2"	23,00	0,91	18	270	180	2610	130,0	5,12	0,400	0,27
19,0	3/4"	31,00	1,22	18	270	180	2610	190,0	7,48	0,740	0,50
25,0	1"	38,00	1,50	18	270	180	2610	250,0	9,84	0,900	0,61
32,0	1 1/4"	46,00	1,81	18	270	180	2610	320,0	12,60	1,190	0,80
38,0	1 1/2"	52,00	2,05	18	270	180	2610	380,0	14,96	1,340	0,91
51,0	2"	67,00	2,64	18	270	180	2610	510,0	20,08	2,130	1,44