


## GOMITO 90° ORIENTABILE MASCHIO JIC - MASCHIO UNF - TIPO 2046\*\*

Materiale: Acciaio al carbonio zincato

Normativa: SAE J514

Filetto: UNF



| Serie JIC  | 20.... [bar] | 21.... [bar] | Ordinazione Completo | Ø Tubo M | Ø Tubo W | W         | L1   | L2   | CH1 | CH2 | JIC 37°   |
|------------|--------------|--------------|----------------------|----------|----------|-----------|------|------|-----|-----|-----------|
| UNIVERSALE | 400          | 400          | 204601.3             | 6        | 1/4      | 7/16-20   | 23   | 27   | 11  | 14  | 7/16-20   |
|            |              |              | 204602.3             | 8        | 5/16     | 1/2-20    | 24   | 29   | 14  | 17  | 1/2-20    |
|            | 350          | 350          | 204603.3             | 10       | 3/8      | 9/16-18   | 27,5 | 32   | 14  | 17  | 9/16-18   |
|            |              |              | 204604.3             | 12       | 1/2      | 3/4-16    | 32   | 37   | 19  | 22  | 3/4-16    |
|            |              |              | 204605.3             | 14-15-16 | 5/8      | 7/8-14    | 37   | 43   | 22  | 27  | 7/8-14    |
|            |              |              | 204606.3             | 18-20    | 3/4      | 1 1/16-12 | 42   | 49,5 | 27  | 32  | 1 1/16-12 |
|            | 290          | 290          | 204607.3             | 25       | 1        | 1 5/16-12 | 46   | 52   | 33  | 41  | 1 5/16-12 |
|            | 240          | 240          | 204608.3             | 30-32    | 1 1/4    | 1 5/8-12  | 53   | 58   | 41  | 50  | 1 5/8-12  |
|            |              |              | 204609.3             | 38       | 1 1/2    | 1 7/8-12  | 59   | 60   | 48  | 55  | 1 7/8-12  |
|            | 350          | 350          | 204610.3             | 6        | 1/4      | 1/2-20    | 24   | 29   | 14  | 17  | 7/16-20   |
|            |              |              | 204611.3             | 6        | 1/4      | 9/16-18   | 24   | 32   | 14  | 17  | 7/16-20   |
|            |              |              | 204612.3             | 8        | 5/16     | 9/16-18   | 24   | 32   | 14  | 17  | 1/2-20    |
|            |              |              | 204613.3             | 10       | 3/8      | 7/16-20   | 27,5 | 28   | 14  | 14  | 9/16-18   |
|            |              |              | 204614.3             | 10       | 3/8      | 1/2-20    | 27,5 | 29   | 14  | 17  | 9/16-18   |
|            |              |              | 204615.3             | 10       | 3/8      | 3/4-16    | 29,5 | 37   | 19  | 22  | 9/16-18   |
|            |              |              | 204616.3             | 10       | 3/8      | 7/8-14    | 31,5 | 43   | 22  | 27  | 9/16-18   |
|            |              |              | 204617.3             | 12       | 1/2      | 9/16-18   | 32   | 36,5 | 19  | 17  | 3/4-16    |
|            |              |              | 204618.3             | 12       | 1/2      | 7/8-14    | 34   | 43   | 22  | 27  | 3/4-16    |
|            |              |              | 204619.3             | 12       | 1/2      | 1 1/16-12 | 36   | 49,5 | 27  | 32  | 3/4-16    |
|            |              |              | 204620.3             | 14-15-16 | 5/8      | 3/4-16    | 37   | 39,5 | 22  | 22  | 7/8-14    |
|            |              |              | 204621.3             | 14-15-16 | 5/8      | 1 1/16-12 | 39   | 49,5 | 27  | 32  | 7/8-14    |
|            |              |              | 204622.3             | 18-20    | 3/4      | 3/4-16    | 42   | 41,5 | 27  | 22  | 1 1/16-12 |
|            |              |              | 204623.3             | 18-20    | 3/4      | 7/8-14    | 42   | 47   | 27  | 27  | 1 1/16-12 |
|            | 290          | 290          | 204624.3             | 18-20    | 3/4      | 1 5/16-12 | 45   | 52   | 33  | 41  | 1 1/16-12 |
|            |              |              | 204625.3             | 25       | 1        | 1 1/16-12 | 46   | 51,5 | 33  | 32  | 1 5/16-12 |
|            | 240          | 240          | 204626.3             | 25       | 1        | 1 5/8-12  | 52   | 58   | 41  | 50  | 1 5/16-12 |

**Note:** Desiderando ordinare il raccordo prescelto in acciaio inox, sostituire nel codice il 20.... iniziale con 21....