


GOMITO 45° ORIENTABILE MASCHIO JIC - MASCHIO GAS CILINDRICO TIPO 2047**

Materiale: Acciaio al carbonio zincato

Normativa: SAE J514

Filetto: Gas cilindrico



Serie JIC	20.... [bar]	21.... [bar]	Ordinazione Completo	Ø Tubo M	Ø Tubo W	G	L1	L2	CH1	CH2	JIC 37°
UNIVERSALE	350	350	204701.3	6	1/4	1/8	19,5	26	11	14	7/16-20
	315	315	204702.3	8	5/16	1/4	20	29	14	19	1/2-20
	250	250	204703.3	10	3/8	1/4	21,5	29	14	19	9/16-18
			204704.3	12	1/2	3/8	25,5	33	19	22	3/4-16
			204705.3	14-15-16	5/8	1/2	29	38,5	22	27	7/8-14
	200	200	204706.3	18-20	3/4	3/4	33	44	27	36	1 1/16-12
			204707.3	25	1	1	38	47	33	41	1 5/16-12
			204708.3	30-32	1 1/4	1 1/4	40	48	41	50	1 5/8-12
	160	160	204709.3	38	1 1/2	1 1/2	46	48	48	55	1 7/8-12
	315	315	204710.3	6	1/4	1/4	20	29	14	19	7/16-20
	250	250	204711.3	6	1/4	3/8	22,5	33	19	22	7/16-20
			204712.3	6	1/4	1/2	23	38,5	22	27	7/16-20
			204713.3	8	5/16	1/8	20	24	14	14	1/2-20
	350	350	204714.3	8	5/16	3/8	22,5	33	19	22	1/2-20
	250	250	204715.3	10	3/8	3/8	23	33	19	22	9/16-18
			204716.3	10	3/8	1/2	23,5	38,5	22	27	9/16-18
			204717.3	12	1/2	1/4	25,5	32,5	19	19	3/4-16
	315	315	204718.3	12	1/2	1/2	26	38,5	22	27	3/4-16
	250	250	204719.3	12	1/2	3/4	27	44	27	36	3/4-16
			204720.3	14-15-16	5/8	3/8	29	33	22	22	7/8-14
			204721.3	14-15-16	5/8	3/4	30	44	27	36	7/8-14
			204722.3	18-20	3/4	1/2	33	43	27	27	1 1/16-12
	200	200	204723.3	18-20	3/4	1	37	47	33	41	1 1/16-12
	250	250	204724.3	25	1	3/4	38	45	33	36	1 5/16-12
	200	200	204725.3	25	1	1 1/4	39	48	41	50	1 5/16-12
			204726.3	30-32	1 1/4	1	40	48	41	41	1 5/8-12
			204727.3	38	1 1/2	1 1/4	46	48	48	50	1 7/8-12

Note: Desiderando ordinare il raccordo prescelto in acciaio inox, sostituire nel codice il 20.... iniziale con 21....