


NIPPLES MASCHIO ORFS - MASCHIO UNF CON O-RING - TIPO 4006**

Materiale: Acciaio al carbonio zincato

Normativa: SAE J514

Filetto: UNF



Serie ORFS	40.... [bar]	41.... [bar]	Ordinazione Completo	Ø Tubo M	Ø Tubo W	W	L1	L2	L3	CH1	ORFS
UNIVERSALE	630	630	400601	6	1/4	7/16-20	18	10	11	17	9/16-18
			400602	8-10	5/16-3/8	9/16-18	20	11	12	19	11/16-16
			400603	12	1/2	3/4-16	22,5	13	14	22	13/16-16
	420	420	400604	14-15-16	5/8	7/8-14	27	15,5	16	27	1-14
			400605	18-20	3/4	1 1/16-12	30	17	18,5	32	13/16-12
			400606	22-25	7/8-1	1 5/16-12	32	17,5	18,5	41	17/16-12
	280	280	400607	28-30-32	1 1/4	1 5/8-12	33,5	17,5	18,5	46	1 11/16-12
			400608	35-38	1 1/2	1 7/8-12	35,5	17,5	18,5	55	2-12
	630	630	400609	6	1/4	1/2-20	18	10	11	17	9/16-18
			400610	6	1/4	9/16-18	18	10	12	19	9/16-18
			400611	6	1/4	3/4-16	19,5	10	14	22	9/16-18
			400612	8-10	5/16-3/8	7/16-20	20	11	11	19	11/16-16
			400613	8-10	5/16-3/8	1/2-20	20	11	11	19	11/16-16
			400614	8-10	5/16-3/8	3/4-16	20,5	11	14	22	11/16-16
			400615	8-10	5/16-3/8	7/8-14	22,5	11	16	27	11/16-16
	420	420	400616	8-10	5/16-3/8	1 1/16-12	24	11	18,5	32	11/16-16
	630	630	400617	12	1/2	9/16-18	22,5	13	12	22	13/16-16
			400618	12	1/2	7/8-14	24,5	13	16	27	13/16-16
	420	420	400619	12	1/2	1 1/16-12	26	13	18,5	32	13/16-16
			400620	12	1/2	1 5/16-12	27,5	13	18,5	41	13/16-16
			400621	14-15-16	5/8	3/4-16	27	15,5	14	27	1-14
			400622	14-15-16	5/8	1 1/16-12	28,5	15,5	18,5	32	1-14
			400623	18-20	3/4	3/4-16	30	17	14	32	13/16-12
			400624	18-20	3/4	7/8-14	30	17	16	32	13/16-12
			400625	18-20	3/4	1 5/16-12	31,5	17	18,5	41	13/16-12
			400626	22-25	7/8-1	1 1/16-12	32	17,5	18,5	41	17/16-12
	280	280	400627	22-25	7/8-1	1 5/8-12	33,5	17,5	18,5	46	17/16-12
			400628	28-30-32	1 1/4	1 5/16-12	33,5	17,5	18,5	46	1 11/16-12
			400629	28-30-32	1 1/4	1 7/8-12	35,5	17,5	18,5	55	1 11/16-12
			400630	35-38	1 1/2	1 5/8-12	35,5	17,5	18,5	55	2-12

Note: Desiderando ordinare il raccordo prescelto in acciaio inox, sostituire nel codice il 40... iniziale con 41...