


GOMITO 90° MASCHIO UNF ORIENTABILE - MASCHIO ORFS - TIPO 4053**

Materiale: Acciaio al carbonio zincato

Normativa: SAE J514C

Filetto UNF/UN-2A



Serie ORFS	40.... [bar]	41.... [bar]	Ordinazione Completo	Ø Tubo M	Ø Tubo W	W	L1	L2	CH1	CH2	ORFS
UNIVERSALE	420	420	405301	6	1/4	7/16-20	21,5	32,5	14	14	9/16-18
			405302	8-10	5/16-3/8	9/16-18	25	37	19	17	11/16-16
			405303	12	1/2	3/4-16	28	40,5	19	22	13/16-16
			405304	14-15-16	5/8	7/8-14	33,5	50	27	27	1-14
			405305	18-20	3/4	1 1/16-12	37,5	55	30	32	13/16-12
	380	380	405306	22-25	7/8-1	1 5/16-12	41,5	59,5	36	41	1 7/16-12
	280	280	405307	28-30-32	1 1/4	1 5/8-12	44,5	62	41	50	1 11/16-12
			405308	35-38	1 1/2	1 7/8-12	49	66	48	55	2-12
	420	420	405309	6	1/4	9/16-18	21,5	34,5	14	17	9/16-18
			405310	6	1/4	3/4-16	23,5	40,5	19	22	9/16-18
			405311	8-10	5/16-3/8	7/16-20	25	35	19	14	11/16-16
			405312	8-10	5/16-3/8	3/4-16	25	40,5	19	22	11/16-16
			405313	8-10	5/16-3/8	7/8-14	28	50	22	27	11/16-16
			405314	8-10	5/16-3/8	1 1/16-12	29,5	55	27	32	11/16-16
			405315	12	1/2	9/16-18	28	37	19	17	13/16-16
			405316	12	1/2	7/8-14	30	50	22	27	13/16-16
			405317	12	1/2	1 1/16-12	31,5	55	27	32	13/16-16
			405318	14-15-16	5/8	3/4-16	33,5	46	27	22	1-14
			405319	14-15-16	5/8	1 1/16-12	33,5	55	27	32	1-14
			405320	18-20	3/4	3/4-16	37,5	47	30	22	13/16-12
			405321	18-20	3/4	7/8-14	37,5	51	30	27	13/16-12
	380	380	405322	18-20	3/4	1 5/16-12	38	59,5	33	41	13/16-12
	420	420	405323	22-25	7/8-1	1 1/16-12	41,5	59	36	32	1 7/16-12
	280	280	405324	22-25	7/8-1	1 5/8-12	44,5	62	41	50	1 7/16-12
			405325	28-30-32	1 1/4	1 5/16-12	44,5	62	41	41	1 11/16-12
			405326	28-30-32	1 1/4	1 7/8-12	48,5	66	48	55	1 11/16-12
			405327	35-38	1 1/2	1 5/8-12	49	66	48	50	2-12

Note: Desiderando ordinare il raccordo prescelto in acciaio inox, sostituire nel codice il 40.... iniziale con 41....