


GOMITO 45° MASCHIO GAS CILINDRICO ORIENTABILE - MASCHIO ORFS - TIPO 4054**

Materiale: Acciaio al carbonio zincato

Normativa: SAE J514C

Filetto Gas cilindrico



Serie ORFS	40.... [bar]	41.... [bar]	Ordinazione Completo	Ø Tubo M	Ø Tubo W	G	L1	L2	CH1	CH2	ORFS
UNIVERSALE	350	350	405401	6	1/4	1/8	16	27,5	14	14	9/16-18
	315	315	405402	8-10	5/16-3/8	1/4	19	32,5	19	19	11/16-16
	250	250	405403	12	1/2	3/8	20,5	33,5	19	22	13/16-16
			405404	14-15-16	5/8	1/2	23,5	43	27	27	1-14
			405405	18-20	3/4	3/4	26	46,5	30	36	13/16-12
	200	200	405406	22-25	7/8-1	1	30	51	36	41	17/16-12
			405407	28-30-32	1 1/4	1 1/4	32	52,5	41	50	1 11/16-12
	160	160	405408	35-38	1 1/2	1 1/2	37	52,5	48	55	2-12
	315	315	405409	6	1/4	1/4	16	31,5	14	19	9/16-18
			405410	6	1/4	3/8	17,5	33,5	19	22	9/16-18
	250	250	405411	8-10	5/16-3/8	3/8	19	33,5	19	22	11/16-16
			405412	8-10	5/16-3/8	1/2	20	43	22	27	11/16-16
	315	315	405413	12	1/2	1/4	20,5	32,5	19	19	13/16-16
	250	250	405414	12	1/2	1/2	21	43	22	27	13/16-16
			405415	12	1/2	3/4	21,5	46,5	27	36	13/16-16
	315	315	405416	14-15-16	5/8	1/4	23,5	36	27	19	1-14
			405417	14-15-16	5/8	3/8	23,5	37	27	22	1-14
	250	250	405418	14-15-16	5/8	3/4	23,5	46,5	27	36	1-14
			405419	14-15-16	5/8	1	28,5	51	33	41	1-14
	315	315	405420	18-20	3/4	1/4	26	40,5	30	19	13/16-12
	250	250	405421	18-20	3/4	1/2	26	44,5	30	27	13/16-12
	200	200	405422	18-20	3/4	1	29,5	51	33	41	13/16-12
	315	315	405423	22-25	7/8-1	1/4	30	41	36	19	17/16-12
	250	250	405424	22-25	7/8-1	3/4	30	47	36	36	17/16-12
			405425	22-25	7/8-1	1 1/4	32	52,5	41	50	17/16-12
	200	200	405426	28-30-32	1 1/4	1	32	52,5	41	41	1 11/16-12
			405427	28-30-32	1 1/4	1 1/2	35,5	52,5	48	55	1 11/16-12

Note: Desiderando ordinare il raccordo prescelto in acciaio inox, sostituire nel codice il 40.... iniziale con 41....