


GOMITO 45° MASCHIO UNF ORIENTABILE - MASCHIO ORFS - TIPO 4056**

Materiale: Acciaio al carbonio zincato

Normativa: SAE J514C

Filetto UNF/UN-2A



Serie ORFS	40.... [bar]	41.... [bar]	Ordinazione Completo	Ø Tubo M	Ø Tubo W	W	L1	L2	CH1	CH2	ORFS
UNIVERSALE	420	420	405601	6	1/4	7/16-20	16	30	14	14	9/16-18
			405602	8-10	5/16-3/8	9/16-18	19	33	19	17	11/16-16
			405603	12	1/2	3/4-16	20,5	36,5	19	22	13/16-16
			405604	14-15-16	5/8	7/8-14	23,5	45	27	27	1-14
			405605	18-20	3/4	1 1/16-12	26	50	30	32	13/16-12
	380	380	405606	22-25	7/8-1	1 5/16-12	30	52,5	36	41	17/16-12
	280	280	405607	28-30-32	1 1/4	1 5/8-12	32	53,5	41	50	1 11/16-12
			405608	35-38	1 1/2	1 7/8-12	37	53,5	48	55	2-12
	420	420	405609	6	1/4	9/16-18	16	33	14	17	9/16-18
			405610	6	1/4	3/4-16	17,5	36,5	19	22	9/16-18
			405611	8-10	5/16-3/8	7/16-20	19	31	19	14	11/16-16
			405612	8-10	5/16-3/8	3/4-16	19	36,5	19	22	11/16-16
			405613	8-10	5/16-3/8	7/8-14	20	45	22	27	11/16-16
			405614	8-10	5/16-3/8	1 1/16-12	19,5	50	27	32	11/16-16
			405615	12	1/2	9/16-18	20,5	32,5	19	17	13/16-16
			405616	12	1/2	7/8-14	21	45	22	27	13/16-16
			405617	12	1/2	1 1/16-12	21,5	50	27	32	13/16-16
			405618	14-15-16	5/8	3/4-16	23,5	40,5	27	22	1-14
			405619	14-15-16	5/8	1 1/16-12	23,5	50	27	32	1-14
			405620	18-20	3/4	3/4-16	26	40,5	30	22	13/16-12
			405621	18-20	3/4	7/8-14	26	46	30	27	13/16-12
	380	380	405622	18-20	3/4	1 5/16-12	29,5	52,5	33	41	13/16-12
	420	420	405623	22-25	7/8-1	1 1/16-12	30	51,5	36	32	17/16-12
			405624	22-25	7/8-1	1 5/8-12	32	53,5	41	50	17/16-12
			405625	28-30-32	1 1/4	1 5/8-12	32	53,5	41	41	1 11/16-12
			405626	28-30-32	1 1/4	1 7/8-12	35,5	53,5	48	55	1 11/16-12
			405627	35-38	1 1/2	1 5/8-12	37	53,5	48	50	2-12

Note: Desiderando ordinare il raccordo prescelto in acciaio inox, sostituire nel codice il 40.... iniziale con 41....