

# GOLDENCRIMP 420 EVO

## ASSEMBLING FOR FIELD REPAIR BENCHTOP CRIMPING MACHINE



### KEY FEATURES

- High crimping force of 420 tonnes
- Robust design for transport and operation in harsh environments
- Protected cylinders for trouble-free operation in high dust environments
- Large opening suitable for large bore hoses
- Easy maintenance due to dust collector foam pads
- Model shown equipped with SC control panel

### CONTROL OPTIONS AVAILABLE ON REQUEST



SC



SCE



SCS

### TECHNICAL SPECIFICATIONS

#### CAPACITY\*

6ws: 3" max.

Industrial: 4" max.

#### CRIMP RANGE

4 - 130 mm (0.157 - 5.118")

#### CRIMP FORCE

420 t

#### OPENING WITH DIES

+48 mm (+1.9 inch)

#### COMPLETE OPENING

178 mm (7.0 inch)

#### MASTER DIE LENGTH

120 mm (4.724 inch)

#### STANDARD DIES

14, 16, 18, 20, 22, 24, 27, 30, 33, 36, 39, 42, 45, 48, 51, 57, 63, 66, 70, 73, 76

#### NOISE LEVEL

&lt;70 dB A

#### MOTOR

5.5 kW

#### VOLTAGES

220/240 V, 3Ph, 50 Hz

380/415 V, 3Ph, 50 Hz

208/240 V, 3Ph, 60 Hz

380/415 V, 3Ph, 60 Hz

#### DIMENSIONS

765 x 500 x 800 mm

(30 x 20 x 32")

#### PACKAGING

745 x 1150 x 945 mm  
(29 x 45 x 37")

#### NET WEIGHT

395 kg (871 lb)

\*Indicative capacities depending on hose and fitting type.

### OPTIONAL



Maintenance Kit



Electrical Footswitch



Die Storage Panel



Die Storage Table



Die Storage Table EVO



Digital caliper



Aluminium Quick Change Gun



Mechanical Backstop



Die Sets for Brake &amp; Air Conditioning Hoses



Marking Dies



Die Storage Panel EVO