

MS 320

ASSEMBLING FOR MASS PRODUCTION STAND TYPE CRIMP MACHINE



KEY FEATURES

- High crimp force
- Large opening
- Safe Crimp System (SCS) control
- Wide family of dies for industrial hoses
- Robust structure
- Fast and ergonomic
- Low noise level

STANDARD



Aluminium Quick Change Gun



SCS Safe Crimp System



Mirror



Electrical Footswitch



Die Storage



Pushing panel

TECHNICAL SPECIFICATIONS

CAPACITY*

2wb: 3" max.
4ws: 2" max.
6ws: 2" max.
Industrial: 4" max.

CRIMP RANGE

4 - 130 mm (0.157 - 5.118")

CRIMP FORCE

320 t

OPENING WITH DIES

+80 mm (+3.149")

COMPLETE OPENING

207 mm (8.149")

MASTER DIE LENGTH

100 mm (3.937")

STANDARD DIES

14, 16, 18, 20, 22, 24, 27, 30, 33, 36, 39, 42, 45, 48, 51, 57, 63, 66, 70, 73, 76

NOISE LEVEL

<65 dB A

MOTOR

5.5 kW / 7.5 kW (Fast Version)

VOLTAGES

220/240 V, 3Ph, 50 Hz

380/415 V, 3Ph, 50 Hz

208/240 V, 3Ph, 60 Hz

380/415 V, 3Ph, 60 Hz

DIMENSIONS

1200 x 1000 x 1650 mm

(47 x 39 x 64")

PACKAGING

1400 x 1100 x 1960 mm

(55 x 43 x 77")

NET WEIGHT

1370 kg (3020 lb)

GROSS WEIGHT

1570 kg (3461 lb)

*Indicative capacities depending on hose and fitting type.

OPTIONAL



Die Storage Panel



Marking Dies



Back View Camera



Digital Caliper



Mechanical Backstop



Side Table



Die Sets for Brake & Air Conditioning Hoses



Barcode Reader