

MS 480

ASSEMBLING FOR MASS PRODUCTION STAND TYPE CRIMP MACHINE



KEY FEATURES

- High crimp force
- Large opening
- Safe Crimp System (SCS) control
- Wide family of dies for industrial hoses
- Long master dies
- Robust
- Low noise level

STANDARD



Aluminium Quick
Change Gun



SCS Safe Crimp
System



Mirror



Electrical Footswitch



Die Storage



Pushing Panel

TECHNICAL SPECIFICATIONS

CAPACITY*

6ws: 3" max.

Industrial: 4" max.

CRIMP RANGE

4 - 160 mm (0.157 - 6.299")

CRIMP FORCE

480 t

OPENING WITH DIES

+85 mm (+3.346")

COMPLETE OPENING

212 mm (8.346")

MASTER DIE LENGTH

125 mm (4.921")

STANDARD DIES

14, 16, 18, 20, 22, 24, 27, 30, 33,
36, 39, 42, 45, 48, 51, 57, 63, 66,
70, 73, 76

NOISE LEVEL

<65 dB A

MOTOR

5.5 kW

VOLTAGES

220/240 V, 3Ph, 50 Hz

380/415 V, 3Ph, 50 Hz

208/240 V, 3Ph, 60 Hz

380/415 V, 3Ph, 60 Hz

DIMENSIONS

1300 x 1050 x 1700 mm

(51 x 41 x 67")

PACKAGING

1400 x 1100 x 1960 mm

(55 x 43 x 77")

NET WEIGHT

1675 kg (3693 lb)

GROSS WEIGHT

1890 kg (4167 lb)

*Indicative capacities depending on hose and fitting type.

OPTIONAL



Die Storage
Panel



Marking Dies



Back View
Camera



Digital Caliper



Mechanical Backstop



Side Table



Die Sets for Brake & Air
Conditioning Hoses



Barcode Reader