

MV 350 / 350 L

FIELD SERVICE & MOBILE / CONTAINER
WORKSHOP MOBILE VAN

KEY FEATURES

- Robust design
- Large opening
- High crimping force
- Ergonomic micrometer
- High crimping speed
- Radial movement of the dies
- Cylinder protection
- Remote head mounting option possible



TECHNICAL SPECIFICATIONS

CAPACITY*

2wb: 3" max.
4ws: 2" max.
6ws: 2" max.
Industrial: 4"

CRIMP RANGE

4 - 130 mm (0.157 - 5.118")

CRIMP FORCE

350 t

OPENING WITH DIES

+54 mm (+2.125")

COMPLETE OPENING

180 mm (7.086")

MASTER DIE LENGTH

115 mm (4.528")

STANDARD DIES

14, 16, 18, 20, 22, 24, 27, 30, 33, 36, 39, 42, 45, 48, 51, 57, 63, 66, 70, 73, 76

NOISE LEVEL

<65 dB A

*Indicative capacities depending on hose and fitting type.

** L Version

MOTOR

2.0 kW

VOLTAGES

12 V

24 V

220/240 V, 3Ph, 50 Hz

380/415 V, 3Ph, 50 Hz

208/240 V, 3Ph, 60 Hz

380/415 V, 3Ph, 60 Hz

DIMENSIONS

650 x 550 x 750 mm

485 x 435 x 390 mm**

PACKAGING

800 x 600 x 830 mm

NET WEIGHT

210 kg / 215 kg**

GROSS WEIGHT

260kg / 230 kg**

DIMENSIONS OF POWER PACK

605 x 318 x 325 mm

OPTIONAL



Maintenance Kit



Battery



Aluminium Quick Change Gun



Die Storage Panel



Marking Dies



Die Sets for Brake & Air Conditioning Hoses



Front Die Storage